

# FLKM 50-PA-MODI-TSX/Q


Order No.: 2294306

The illustration shows versions FLKM 50-PA-MODI-TSX/Q and FLKM 50/ 4-FLK14/PA-MODI-TSX/Q



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2294306>

VARIOFACE front adapter, for Schneider Electric MODICON TSX Quantum, 1 x 32 channels can be connected

Commercial data	
GTIN (EAN)	 4 017918 132699
sales group	I601
Pack	1 pcs.
Customs tariff	85369010
Catalog page information	Page 204 (IF-2009)

### Product notes

WEEE/RoHS-compliant since:  
08/02/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

General	
Nominal voltage $U_N$	< 50 V AC 60 V DC
Channels which can be connected	32
Connection type, plug connector	Flat-ribbon cable plug connector in acc. with IEC 60603-13

Number of plug connectors	1
No. of positions, plug connector	50
Number of positions	50
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Mounting position	Any
Standards/regulations	IEC 60664
	DIN EN 50178
	IEC 62103
Max. permissible current	1 A (per path)
	4 A (per connection, supply via separate power supply)
Name	Air and creepage distances between the power circuits
Standards/regulations	DIN EN 50178
Rated surge voltage / insulation	0.6 kV / Basic isolation
Rated insulation voltage	63 V
Pollution degree	2
Surge voltage category	II
Supported controller	Schneider Electric MODICON TSX QUANTUM

Supported I/O card	DDI 353
	DDI 841
	DDI 853
	DAI 340
	DAI 353
	DAI 440
	DAI 453
	DDO 353
	DDM 390
	ACI 030
	ACI 040
	ATI 030
	ARI 030
	AVI 030
	ACO 020
	ACO 130
	AVO 020
	EHC 105
	EHC 202

### Certificates / Approvals




Certification

CUL, GOST, UL

## Diagrams/Drawings

### Circuit diagram



Connection scheme FLKM 50-PA-MODI-TSX/Q

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;