



NUMBER OF POSITIONS	DIMENSION	
	A	B
06	5.08	12.32
08	7.62	14.86
10	10.16	17.40
12	12.7	19.94
14	15.24	22.48
16	17.78	25.02
18	20.32	27.56
20	22.86	30.10
24	27.94	35.18
26	30.48	37.72
28	33.02	40.26
30	35.56	42.80
34	40.64	47.88
40	48.26	55.5
50	60.96	68.20
60	73.66	80.90
64	78.74	85.98

MATERILA&FINISH  
 insulator:PBT Glass Fiber<UL94V-0>BLAKC  
 Contact:Brass  
 Contact: Tin-Plated Over Nickel  
 SPECIFICATIONS  
 Current Rating:1A AV,DC  
 Voltage Rating:250V AC,DC  
 Temperature Range:-40°C TO +150°C  
 Contact Resistance:20mΩ Min  
 Insulation Resistance:1000mΩ Min  
 withstanding Voltage: 500V AC/Min

UNLESS OTHERWISE SPECIFIED TOLERANCE :		<b>CnC Tech, LLC</b> Industrial Cable and Connector Technology			
X.	±0.20				
X.X	±0.15	DO NOT SCALE DRAWING		PART NO. 3030-01-XX-0102	
X.XX	±0.10			SIZE A	UNIT MM
DRAWN BY	Kevin		TITLE 2.54/IDC		REV A0
CHECKED BY			SCALE	THIRD ANGLE PROJECTION	PAGE 1 OF 1
APPROVED BY	[Signature]		DATE 2005/07/17		
DWG NO.			ITEM NO.		