Europe connectors - EC 10 BK - 3240177

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Polypropylene Europe terminal strip, black, for connecting solid conductors and stranded conductors with and without ferrules with a cross section of 1 to 10 mm²

Product Features

- The polypropylene insulating housing enables individual positions to be disconnected simply by twisting and without the need for tools
- The high-quality metal parts, which feature corrosion-resistant surfaces, are fixed securely in the housing
- The prismatic clamping part facilitates conductor entry and reliable contact can be established even for conductors without ferrules

Key commercial data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	43.09 GRM
Custom tariff number	85369010
Country of origin	Austria

Technical data

General

Number of levels	1
Number of connections	24
Color	black
Insulating material	PP
Inflammability class according to UL 94	-
Maximum load current (lower level)	57 A (with 10 mm² conductor cross section)
Nominal current I_N (lower level)	57 A (with 10 mm² conductor cross section)
Nominal voltage U_N	450 V
Maximum load current (upper level)	57 A (with 10 mm² conductor cross section)
Number of positions	12

Dimensions

Width	17.3 mm