



JKL PART NUMBER	-A- LENGTH	LCD HIGH OUTPUT WHITE RGB COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms) TYP.	OPERATING LAMP VOLTAGE VL (Vrms) TYP.	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF2698-20B	98±2.0	5,400°k x = .336 y = .353	690 @ 0°C	275	5 ± 1	30,000 TYP.	35,000 AVG.
BF26188-20B	188±3.0		1115 @ 0°C	405			
BF26214-20B	214±2.0		1150 @ 0°C	460			
BF26285-20B	285±1.5		1525 @ 0°C	610			
BF26318-20B	318±1.5		1710 @ 0°C	685			
BF26360-20B	360±1.5		1940 @ 0°C	775			

NOTES:

* RATED LIFE IS DEFINED AS THE POINT WHICH INTENSITY BECOMES 50% OF THE INITIAL RATING.

RATING AT 25°C UNLESS OTHERWISE SPECIFIED.

			METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- REF. 2 PL +/- REF. ANGLE +/- REF.		JKL COMPONENTS CORPORATION			
DRAWN BY L. WENGSTROM			APPVD BY L.R.		DATE 3/25/08		TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP	
WIRE LENGTH TOLERANCE CHANGE 3/25/08			ADD PART BF2698-20B 2/1/04		ELECTRICAL CHNG. & ADD BF26318 & BF26360 10/20/04		RELEASED TO CAD MULTI LIST 8/14/03	
REV. NO. DESCRIPTION/ECO NUMBER APPVD DATE			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE		DRAWING NO. BF 26-20B	
			RELEASED DATE 8/14/03		REVISION DATE 3/25/08		REV. NO. D SHEET 1 OF 1	