6000 SP Splash Resistant Rocker Switches





Key Features

- Ratings up to 20A, 277Vac
- O Positive switch action
- Distinctive styling
- Illuminated & nonilluminated
- Single pole
- Panel cut out: 30.1 x 11.1mm

Approvals and specifications

3 European 16(4)A 250Vac T125, 10A 400Vac T125

UL = 20A 277Vac, 1 1/2HP 250Vac 1HP 125Vac CSA = 20A 277Vac, 1HP 125Vac, 1/2HP 125Vac

3mm contact gap with Positive Break switching. Call factory for IP details.

Vary with Function

Approvals & ratings vary with function ON OFF Switches - ON when pressed over terminals 3.



Terminal	Function	Rocker	Body	Body Colour	Rocker Colour	Lamp Voltage
C	6000 • • • • • • • • • • • • • • • • • •	Softline Matt	Panel cut-out ** Bezel R2,0 30,0/ 30,1 11,0/11,1 14,0	B Black	Lit (DP) A Amber	Blank
6.3 x 0.8	ON - OFF (momentary ON)		Cut-outs must be punched in the direction of insertion	W White	C Clear	2 125V Neon
H	6002 ON - OFF (momentary OFF)	Softline Matt			G Green	3 250V Neon
9.7 4.8 × 0.8	6003 • • • • • • • • • • • • • • • • • • •	P Lit window Matt			R Red	5 12Vdc LED (P Rocker)
Screw & Clamp N/A for assemblies with 3 terminals	6008 ON - OFF Lit (Unswitched neutral)				Lit (DP)	6 24Vdc LED (P Rocker)
	6009 ON - OFF (momentary ON) Lit (Unswitched neutral)				R Red	7 12V Filament
	6010 ON - ON				W White	8 24Vdc Filament
	6011 ON - ON (momentary 1 side)					



Integral Splash Resistance



Current carrying parts are protected from moisture.
Droplets which may enter the switch are channelled out through ports in the switch body.
For IP65 see options below

Dimensions



Panel thickness L 0.75 to 2.5mm

** For cut-out details on momentary switches call sales

Legend	Legend Colour	Options
 Blank	 Blank	G74 Protective Cover
1223	B Black	Finish Matt is standard. Colour Call sales for custom colours. A full range is available for large orders.
	W White	Legend printing Select from the examples or call sales for custom legends. Lamp voltage Call sales for details. Protective cover A snap on cover is available (add G after body code), this reduces panel thickness by 2mm.
		Panel sealing washer W46 is available, this reduces panel thickness by 1.2mm. Covers are not suitable for momentary types. For all options call the factory

Examples







TC6000AL - - -



☐ C6010AL - - -



☐ C6003AL - - -



TC6003PL - - -



TC6030AL - - -