


CCPD-575 Model
5×7.5 mm SMD, 3.3V, LVPECL

CCPD-575 5×7.5mm SMD Ultra-Low Phase Noise LVPECL Clock Oscillator



Model CCPD-575 has an industry leading phase noise for an LVPECL oscillator. The noise floor is typically @ -162 dBc/Hz! This is at least 15 dB lower phase noise than most LVPECL oscillators on the market today. Close-in phase noise is also excellent @ -90 dBc/Hz for the 100 MHz variant. This overall ultra-low phase noise translates to a typical phase jitter of 65 fs RMS (12 kHz to 20 MHz) at 156.250 MHz.



5×7.5mm SMD

Applications:

**Digital Video
SONET/SDH/DWDM
Storage Area Networks
Broadband Access
Ethernet, Gigabit Ethernet**

Rev: T
Date: 02-Oct-2017
Page 1 of 4

CCPD-575 5×7.5mm SMD Ultra-Low Phase Noise LVPECL Clock Oscillator

CCPD-575 Model
5×7.5 mm SMD, 3.3V, LVPECL


Frequency Range:	50.000 MHz to 156.250 MHz*
Frequency Stability Options:	±20ppm, ±25ppm, ±50ppm
Operating Temperature Range:	-40°C to +85°C
Storage Temperature Range:	-45°C to 90°C
Input Voltage:	3.3V ± 0.3V
Input Current:	80mA Typical, 88mA Max
Output:	Differential LVPECL
Symmetry:	40/60% Max @ zero crossing point
Rise/Fall Time:	300 ps Max (20% to 80%)
Logic Terminated to Vdd-2V into 50 Ω:	
Output Low Voltage:	"0"=1.37 Min, 1.74 Max
Output High Voltage:	"1"=2.05 Min, 2.54 Max
Disable Time:	200 ns Max
Enable Time:	200 ms Max
Phase Jitter: 12kHz~20MHz	65 fs RMS Typical @ 156.250 MHz
Phase Noise: (See Plot Below)	
Sub-harmonics:	None
Aging:	<3ppm 1 st year, <1ppm every year thereafter

*Standard Frequencies (MHz)
80.000
100.000
122.880
125.000
156.250



Part Number Example: CCPD-575X-20-100.000 3.3V, -40/85°C, ±20ppm, 100.000 MHz

100.000 MHz LVPECL 3.3V



Rev: T
Date: 02-Oct-2017
Page 2 of 4


Specifications subject to change without notice.

CCPD-575 5×7.5mm SMD Ultra-Low Phase Noise LVPECL Clock Oscillator


CCPD-575 Model
5×7.5 mm SMD, 3.3V, LVPECL



122.880 MHz LVPECL 3.3V



156.250 MHz LVPECL 3.3V



Rev: T
Date: 02-Oct-2017
Page 3 of 4

CCPD-575 5×7.5mm SMD

Ultra-Low Phase Noise


LVPECL Clock Oscillator




CCPD-575 Model
5×7.5 mm SMD, 3.3V, LVPECL

Mechanical:	
Shock:	MIL-STD-883, Method 2002, Condition B
Solderability:	MIL-STD-883, Method 2003
Vibration:	MIL-STD-883, Method 2007, Condition A
Solvent Resistance:	MIL-STD-202, Method 215
Resistance to Soldering Heat:	MIL-STD-202, Method 210, Condition I or J
Environmental:	
Thermal Shock:	MIL-STD-883, Method 1011, Condition A
Moisture Resistance:	MIL-STD-883, Method 1004

RECOMMENDED REFLOW SOLDERING PROFILE



NOTE: Reflow Profile with 240°C peak also acceptable.





Dimensions inches (mm)
All dimensions are Max unless otherwise specified.



Enable/Disable	
Function pin 1	Output pin
Open or N/C "1" level 2.0V Min "0" level 0.8V Max	Active Active High Z

Denotes pad 1
TT=Tolerance YYWW=Date Code XX=Lot Code

SUGGESTED PAD LAYOUT



PIN	Connection
1	Enable/Disable
2	N/C
3	GND
4	Output
5	Comp Output
6	Vcc

PAD FINISH: Immersion Gold (ENIG); 5 micro inches maximum

Rev: T
Date: 02-Oct-2017
Page 4 of 4