



#### www.lemo.com

### **SUMMARY**

#### # Wires

 Low
 0

 High
 0

 Coax
 1

Triax 0

Quad 0

Fiber 0

Fluidic 0

Series 00

Termination type Male solder

IP rating 50

 Cable Ø
 0.00 - 2.30 mm

 Matching parts
 ERA.00.250.CTL

**Status** active

Alternative part



Image is for illustrative purpose only

#### **Download**

Request a quote

Catalog

## **TECHNICAL DETAILS**

#### **Mechanics**

Shell Style/Model FFS\*: Straight plug with cable crimping

Keying Circular (can rotate)

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Cable Fixing : 0 - 2.3 mm

Variant

Weight 3.22 g

#### **Performance**

Configuration 0.25 : 1 Coax (50 Ohm)

Insulator T: PTFE
Rated Current 4 Amps

### **Specifications**

Contact Type: Coaxial 50 Ohm (Solder)

Max. Matings: 5000

Contact Dia.: 0.7 mm (0.028in)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Bucket Dia.: 0.6 mm (0.024in) Test voltage: 2.1 kV (rms)

R (max): 6.1 mOhm

Vtest: 2100 V (AC), 3000 V (DC)

Impedance: 50 Ohm VSWR: 1.09 + 0.11 \* f/GHz Cable type: RG 196 A/U


#### **Others**

Endurance (Shell): 5000 mating cycles

F ret (min): 100 N IP Rating: 50

## **DRAWINGS**

#### **Draws**







#### **Dimensions**

	А	L	М
mm.	6.4	31	23
in.	0,25	1,22	0,91

# **RECOMMENDED BY LEMO**

#### Tools

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Die Tool: DPE.99.123.1K Spanner wrench: DCP.99.055.TC

### **Cables**

178 190	PTFE	Brown	
196 270	PTFE	White	
CCX.50.030.083.180B		White	
CCX.50.RG1.78BU18M	FEP	Brown	
CCX.50.RG1.78BU18M	PTFE	Brown	
CCX.50.RG1.96AU19B	PTFE	White	
CCX.50.RG1.96AU20B	PFA	White	

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.