

# FFS.00.250.CTCE24

## SUMMARY

### # Wires

# Wires		
Low	0	
High	0	
Coax	1	Image is for illustrative purpose only
Triax	0	Download
Quad	0	Request a quote
Fiber	0	Catalog
Fluidic	0	<u>_</u>
Series	00	
Termination type	Male crimp	
IP rating	50	
Cable Ø	0.00 - 2.30 mm	
Matching parts		
Status	active	
Alternative part		

### **TECHNICAL DETAILS**

### **Mechanics**

Shell Style/	Model	FFS*: Straight plug with cable crimping	
Keying		Circular (can rotate)	
Housing Ma	terial	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces	
Cable Fixing	g	: 0 - 2.3 mm	
Variant			
Weight		3.22 g	
Performance	e		
Configuration	on	0.25 : 1 Coax (50 Ohm)	
Insulator		T: PTFE	

# Specifications

**Rated Current** 

Contact Type: Coaxial 50 Ohm (Crimp) Max. Matings: 5000 Contact Retention: 18 N

4 Amps

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Contact Dia.: 0.7 mm (0.028in) Bucket Dia.: 0.6 mm (0.024in) Test voltage: 2.1 kV (rms) R (max): 6.1 mOhm Vtest: 2100 V (AC), 3000 V (DC)


Impedance: 50 Ohm VSWR: 1.09 + 0.11 \* f/GHz Cable type: RG 196 A/U

### Others

Endurance (Shell): 5000 mating cycles F ret (min): 100 N IP Rating: 50

### DRAWINGS

#### Draws



#### Dimensions

	А	L	м
mm.	6.4	31	23
in.	0,25	1,22	0,91

### **RECOMMENDED BY LEMO**

### Tools

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Crimp Tool: DPC.91.701.V Die Tool: DPE.99.123.1K Spanner wrench: DCP.99.055.TC

### Cables

178 190	PTFE	Brown
196 270	PTFE	White
CCX.50.030.083.180B		White
CCX.50.RG1.78BU18M	FEP	Brown
CCX.50.RG1.78BU18M	PTFE	Brown
CCX.50.RG1.96AU19B	PTFE	White
CCX.50.RG1.96AU20B	PFA	White

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.