

SUMMARY

Wires

Low	67
High	0
Coax	0
Triax	0
Quad	0
Fiber	0
Fluidic	0

Series	1R
Termination type	Male crimp
IP rating	50
Cable Ø	2.00 - 9.20 mm
Matching parts	
Status	active
Alternative part	



Image is for illustrative purpose only

Download

[Request a quote](#)

[Catalog](#)

TECHNICAL DETAILS

Mechanics

Shell Style/Model	FGG*: Straight plug, key (G) or key (A), with cable collet
Keying	3 keys (alpha=50,beta=30, plug: male contacts, receptacle: female contacts)
Housing Material	Crastin® PBT (Polybutylene terephthalate), gray
Cable Fixing	∅ 2 - 9.2 mm
Variant	
Weight	17.22 g

Performance

Configuration	1R.367 : 67 low voltage
Insulator	L: PEEK (UL 94 / V-0/3.2, depends on material thickness)
Rated Current	0.5 Amps

Specifications

Contact Type: Crimp
Test voltage (kV rms) Contact-contact: 0.6



LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Others

IP Rating: 50

DRAWINGS

Draws



Dimensions

	A	B	L
mm.	24.5	9	31.5
in.	0,96	0,35	1,24

RECOMMENDED BY LEMO

Tools

Crimp Tool: DPC.91.701.V
Positionner: DCE.91.050.BVC
Extractor: DCF.91.050.2LT

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.