

www.lemo.com

# FGG.2B.013.CLAD72

## **SUMMARY**

#### # Wires

 Low
 0

 High
 0

 Coax
 0

 Triax
 0

 Quad
 0

 Fiber
 0

 Fluidic
 1

Series 2B

Termination type Male solder

IP rating 50

Cable Ø 6.30 - 7.20 mm

Matching parts EGG.2B.013.CLL

**Status** active

Alternative part



Image is for illustrative purpose only

### **Download**

Request a quote

Catalog

See video assembly instructions

## **TECHNICAL DETAILS**

## **Mechanics**

Shell Style/Model FG\*: Straight plug, cable collet

Keying 1 key (alpha=0, plug: male contacts, receptacle: female contacts)

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

**Cable Fixing** D72: 6.3 - 7.2 mm

Variant

**Weight** 32.07 g

### **Performance**

**Configuration** 2B.013 : 1 Fluidic, 6 Low Voltage

Insulator L: PEEK (UL 94 / V-0/3.2, depends on material thickness)

Rated Current 5 Amps

## **Specifications**

Contact Type: Solder

Vtest: 1200 V (AC), 1800 V (DC) Contact Inner Dia.: 1.6 mm (0.063in)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Tube Inner Dia.: 3.2 mm (0.126in)

### **Others**

Temp (min / max):  $-55^{\circ}$ C /  $+250^{\circ}$ C


Humidity (max): <=95% [at 60 deg C /140 F]

Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [ 6 ms] Salt Spray Corrosion: >1000 hr Climatical Category: 50/175/21 Shielding (min): 75 dB (10 MHz) Shielding (min): 40 dB (1 GHz)

IP Rating: 50

## **DRAWINGS**

### **Draws**







### **Dimensions**

	А	L	М	S1	S2
mm.	15	50	38	13	12
in.	0,59	1,97	1,50	0,51	0,47

## **RECOMMENDED BY LEMO**

## **Tools**

Spanner wrench: MTZ.2B.220.120

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Caps: BFG.2B.100.PCSG Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.