

www.lemo.com

# FLA.00.250.CTAC27

### **SUMMARY**

#### # Wires

 Low
 0

 High
 0

 Coax
 1

 Triax
 0

 Quad
 0

 Fiber
 0

 Fluidic
 0

Series 00

Termination type Male solder

IP rating 50

Cable Ø 2.30 - 2.70 mm

Matching parts ERA.00.250.CTL

**Status** active

Alternative part



Image is for illustrative purpose only

#### **Download**

Request a quote

Catalog

## **TECHNICAL DETAILS**

#### **Mechanics**

Shell Style/Model FLA\*: Elbow plug with cable collet

Keying Circular (can rotate)

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Cable Fixing C27: 2.3 - 2.7 mm

Variant

Weight 5.05 g

#### **Performance**

Configuration 0.25 : 1 Coax (50 Ohm)

Insulator T: PTFE
Rated Current 4 Amps

#### **Specifications**

Contact Type: Coaxial 50 Ohm (Solder)

Max. Matings: 5000

Contact Dia.: 0.7 mm (0.028in)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Bucket Dia.: 0.6 mm (0.024in) Test voltage: 2.1 kV (rms)

R (max): 6.1 mOhm

Vtest: 2100 V (AC), 3000 V (DC)

Impedance: 50 Ohm VSWR: 1.09 + 0.11 \* f/GHz Cable type: RG 179 B/U


#### **Others**

Endurance (Shell): 5000 mating cycles

F ret (min): 100 N IP Rating: 50

### **DRAWINGS**

#### **Draws**







#### **Dimensions**

	А	L	М
mm.	9	17.5	9.5
in.	0,35	0,69	0,37

## **RECOMMENDED BY LEMO**

#### Tools

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Spanner wrench: DCD.00.003.PA050

#### **Cables**

017 450	COPOLYMER	Black	
018 700	PTFE	White	
018 800	PTFE	White	
CCX.50.RG0.58AU14B	FEP	White	
CCX.50.RG1.74-U25N	PVC	Black	
CCX.50.RG1.74U25N	PVC	Black	
CCX.50.RG1.88AU24B	TFE	White	
CCX.50.RG1.88AU26B	PFA	White	
CCX.50.RG1.88AU26B	PTFE	White	
CCX.50.RG3.16BU26M	FEP	Brown	
CCX.75.RG1.79BU26M	FEP	Brown	
CCX.75.RG1.87AU26B	PFA	White	
CCX.75.RG1.87AU27B	PTFE	White	

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.