

**POWER™
STRIP 30**

CC46L-1416-01-L

IMS5-02-02

MPT-04-6.30-01-L-V

MPT-04-01-01-L-RA-SD

(5.00 mm) .1969"

IMS5, CC46L, CC46R, MPT SERIES

DISCRETE WIRE COMPONENTS & TOOLING

SPECIFICATIONS

For complete specifications see www.samtec.com?IMS5, www.samtec.com?CC46L or www.samtec.com?CC46R

TOOLING

- Hand tool: CAT-HT-246-1416-14
- Mini Applicator: CAT-MC-246-1416-XX-02
- Extraction Tool: CAT-EX-MPSS-01

TYPE	NO. OF POSITIONS	02	TYPE	1416	01	PLATING OPTION
IMS5 = Body, Loose	-02, -03, -04, -06, -08	-02 = Plastic Latch	CC46L = Contact, Loose CC46R = Contact, Full Reel	-1416 = 14 to 16 AWG		-L = 10 μ" (0.25 μm) Gold on contact -T = Matte Tin
<p>Insulator & Latch Material: Nylon 6/6</p>			<p>Contact Material: Copper Alloy</p>			

Mates with: MPS, MPSS

SPECIFICATIONS

For complete specifications see www.samtec.com?MPT

Insulator Material: Black LCP
Terminal Material: Copper Alloy
Plating: Sn or Au over 50 μ" (1.27 μm) Ni
Operating Temp Range: -55 °C to +105 °C with Tin; -55 °C to +125 °C with Gold
Voltage Rating: 600 VAC/848 VDC
RoHS Compliant: Yes
Lead-Free Solderable: Yes

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



Note: Some lengths, styles and options are non-standard, non-returnable.

MPT	POWER PINS	LEAD STYLE	TAIL LENGTH	PLATING OPTION	TAIL	SD
-02, -03, -04, -06, -08	-6.30 = (6.30 mm) 0.248" (-V only) -01 = Right-angle (-RA only)	-01 = Use with (1.60 mm) .062" Thick PCB -03 = Use with (2.36 mm) .093" Thick PCB	-L = 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail -T = Matte Tin	-V = Vertical -RA = Right-angle	-SD = Screw Down (-RA only)	
<p>No. of positions x (5.00) .1969 + (7.55) .297</p> <p>-V SHOWN -RA-SD SHOWN</p>						

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.