

www.lemo.com

# PCA.1S.650.CTLC52

### **SUMMARY**

#### # Wires

**Triax** 

 Low
 0

 High
 0

 Coax
 0

Quad 0 Fiber 0

Fluidic 0

Series 1S

**Termination type** Female solder

IP rating 50

 Cable Ø
 4.20 - 5.20 mm

 Matching parts
 FFA.1S.650.CLAC52

**Status** active

Alternative part



Image is for illustrative purpose only

#### **Download**

Request a quote

Catalog

## **TECHNICAL DETAILS**

#### **Mechanics**

Shell Style/Model PCA\*: Free receptacle, cable collet

**Keying** Circular (can rotate), plug has male contact(s)

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Cable Fixing : 4.2 - 5.2 mm

Variant

**Weight** 19.85 g

#### **Performance**

Configuration 1S.650: 1 Triax (50 Ohm)

Insulator T: PTFE Rated Current 6 Amps

#### **Specifications**

Contact Type: Triaxial 50 Ohm (Solder)

Max. Matings: 1000

Contact Dia.: 0.9 mm (0.034in)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Vtest: 1200 V (AC), 1700 V (DC)

Impedance: 50 Ohm VSWR: 1.01 + 0.17 \* f/GHz

Cable type: RGT 178, RGT 174, Belden 9222

#### **Others**

Endurance (Shell): 5000 mating cycles Temp (min / max): -55°C / +250°C


Humidity (max): <=95% [at 60 deg C /140 F]

Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [ 6 ms] Salt Spray Corrosion: >144 hr Climatical Category: 50/175/21 Shielding (min): 75 dB (10 MHz) Shielding (min): 40 dB (1 GHz)

IP Rating: 50

### **DRAWINGS**

#### **Draws**







#### **Dimensions**

	А	С	L	S2
mm.	11.9	6.2	40.5	8.5
in.	0,47	0,24	1,59	0,33

## **RECOMMENDED BY LEMO**

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

#### **Tools**

Spanner wrench: DCD.1S.015.PA085

#### **Cables**

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.