



www.lemo.com

SUMMARY

Wires

 Low
 6

 High
 0

 Coax
 0

 Triax
 0

 Quad
 0

 Fiber
 0

 Fluidic
 0

Series F

Termination type Female print PCB

IP rating 50

Cable Ø 0.00 - 0.00 mm

Matching parts

Status active

Alternative part



Image is for illustrative purpose only

Download

Request a quote

Catalog

TECHNICAL DETAILS

Mechanics

 $\textbf{Shell Style/Model} \qquad \text{PP*: Elbow receptacle key (G) or keys (A,B,C) for printed circuit}$

Keying 1 key (alpha=0; Plug: male contact; Receptacle: female contact)

Housing Material PSU (Polysulfone), black

Cable Fixing : 0 - 0 mm

Variant

Weight 6.03 g

Performance

Configuration 1P.M06: 6 Low Voltage

Insulator

Rated Current 6 Amps

Specifications

Contact Type: Print (straight)

Max. Matings: 2000

Contact Dia.: 0.7 mm (0.0275in)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

R (max): 6.5 mOhm

Test voltage (kV rms) Contact-contact: 1.05


Air clearance min. (mm) or Creepage distance min. (mm): 0.85

Others

F ret (min): 50 N F ret (max): 150 N IP Rating: 50

DRAWINGS

Draws







Dimensions

	А	В	Н	L	М
mm.	13.4	15.9	17.5	30.2	14.8
in.	0,53	0,63	0,69	1,19	0,58

RECOMMENDED BY LEMO

Tools

None

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

