


REV.	DESCRIPTION	DATE
A	NEW DRAWING	4/20/2006



SPECIFICATIONS:
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 100M OHMS MIN: 500V DC
 VOLTAGE WITHSTAND: 500V AC R.M.S. FOR 1 MINUTE
 LIFE: 5,000 CYCLES
 OPERATING TEMP: -20° ~ +85°C




TOLERANCE:
 ±0.3mm UNLESS OTHERWISE
 SPECIFIED



9615 SW Allen Blvd., Ste. 103
 Beaverton, OR 97005
 Phone: 503-643-4899
 800-275-4899
 Fax: 503-372-1266
 Website: www.cui.com

COLOR INDEX	
PART NO.	INPUT X1 INPUT X2 INPUT X3
RCJ-33234	Red Color White Color Yellow Color
RCJ-33X1 X2 X3	Color X1 Color X2 Color X3

MODEL NO.	RCJ-33XXX	MATERIAL	PLATING
SCHEMATIC	1 Black	Brass	Nickel
	2 Red	Brass	Silver
	3 White	Brass	Silver
	4 Yellow	Brass	Silver
	5 Blue	ABS	Black Color
	6 Green	ABS	Black Color
	7 Orange	PBT	see color index



TITLE:	RCA Jack, Dual, Rt Angle, PCB Mount, Vert.	REV:	A
PART NO.	RCJ-33XXX	UNITS:	MM [INCHES]
DRAWN BY:	ZRJ	APPROVED BY:	
PC FILE NAME:	RCJ-33XXX	SCALE:	1:1