



Fxx\*1)P0Gy\*2)  
e.g. F09P0G1

\*1) xx No. of contacts 09, 15, 25 or 37  
\*2) y for performance classes 1, 2 or 3  
(contact cycle for G1/G2/G3 = 500/200/50)

xx	A [mm]	B [mm]	C [mm]
09	30.8	16.9	25
15	39.1	25.2	33.3
25	53	38.9	47.04
37	69.3	55.3	63.5

② RoHS compliant

No.	St.	Part	Type Description/Material	Surface plating/Colour/Class
3	xx	Signal contact	P0 / Brass	AWG 20 / G1/G2/G3
2	1	Shell	Steel	tin plated
1	1	Insulator	PBT (-55°C - +125°C)	white

②	3	xx	Signal contact	P0 / Brass	AWG 20 / G1/G2/G3
	2	1	Shell	Steel	tin plated
	1	1	Insulator	PBT (-55°C - +125°C)	white
	No.	St.	Part	Type Description/Material	Surface plating/Colour/Class
				Measurement without tolerance occ. to ISO 2768-m	SCALE 2:1
				NAME / DATE	TITLE
				DRAWN Denzinger 14-10-2002	D-Sub Miniature Connector
				CHECKED fflöBmann 24-08-2006	
				<b>FCT</b> a molex company	DWG.NO.
	2	24-08-2006	21889		FxxP0Gy
	1				REV. 2
REV.	DATE	CH.-NO.	ORIGINAL: DIN A3-DRAWING AS A FILE	REPLACEMENT FOR:	PAGES 1

COMMENT: ALL RIGHTS ARE RESERVED BY US FOR THIS DRAWING. WITHOUT OUR PRIOR CONSENT, IT MAY NEITHER BE DUPLICATED NOR MADE AVAILABLE TO A THIRD PARTY. AND IT ALSO MAY NOT BE IMPROPERLY USED BY THE RECEIVER, OR A THIRD PARTY.