

## Feed-through terminal block - USSTD 6 - 3070325

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Feed-through terminal block, Connection method: Screw connection with spring support, Cross section: 0.2 mm<sup>2</sup> - 10 mm<sup>2</sup>, AWG: 24 - 8, Width: 8.2 mm, Color: gray, Mounting type: NS 35/7,5, NS 35/15, NS 32

### Product Features

- Can be fitted on both sides with fixed bridges as well as test sockets with 4 mm diameter
- Terminal block and accessories are touch proof according to BGV A2



### Key commercial data

|                                      |           |
|--------------------------------------|-----------|
| Packing unit                         | 1 1       |
| Minimum order quantity               | 50 1      |
| Weight per Piece (excluding packing) | 23.09 GRM |
| Custom tariff number                 | 85369010  |
| Country of origin                    | Poland    |

### Technical data

#### General

|   |  |
|---|--|
| Number of levels                        | 1  |
| Number of connections                   | 2  |
| Color                                   | gray   |
| Insulating material                     | PA   |
| Inflammability class according to UL 94 | V0   |
| Maximum load current                    | 57 A (with 10 mm <sup>2</sup> conductor cross section) |
| Rated surge voltage                     | 6 kV   |
| Pollution degree                        | 3  |
| Surge voltage category                  | III  |
| Insulating material group               | I  |
| Connection in acc. with standard        | IEC 60947-7-1  |

## Feed-through terminal block - USSTD 6 - 3070325

### Technical data

#### General

|   |                                     |
|---|-------------------------------------|
| Nominal current $I_N$   | 41 A                                |
| Nominal voltage $U_N$   | 500 V                               |
| Open side panel   | ja                                  |
| Shock protection test specification   | DIN EN 50274 (VDE 0660-514):2002-11 |
| Back of the hand protection   | guaranteed                          |
| Finger protection   | guaranteed                          |
| Surge voltage test setpoint   | 7.3 kV                              |
| Result of surge voltage test  | Test passed                         |
| Power frequency withstand voltage setpoint                                      | 1.89 kV                             |
| Result of power-frequency withstand voltage test                                | Test passed                         |
| Checking the mechanical stability of terminal points (5 x conductor connection) | Test passed                         |
| Bending test rotation speed   | 10 rpm                              |
| Bending test turns  | 135                                 |
| Bending test conductor cross section/weight                                     | 0.2 mm <sup>2</sup> / 0.2 kg        |
|   | 6 mm <sup>2</sup> / 1.4 kg          |
|   | 10 mm <sup>2</sup> / 2 kg           |
|   | 2.5 mm <sup>2</sup> / 0.7 kg        |
| Result of bending test  | Test passed                         |
| Conductor cross section tensile test  | 0.2 mm <sup>2</sup>                 |
| Tractive force setpoint   | 10 N                                |
| Conductor cross section tensile test  | 6 mm <sup>2</sup>                   |
| Tractive force setpoint   | 80 N                                |
| Conductor cross section tensile test  | 10 mm <sup>2</sup>                  |
| Tractive force setpoint   | 90 N                                |
| Tensile test result   | Test passed                         |
| Tight fit on carrier  | NS 35/NS 32                         |
| Setpoint  | 5 N                                 |
| Result of tight fit test  | Test passed                         |
| Requirements, voltage drop  | ≤ 3.2 mV                            |
| Result of voltage drop test   | Test passed                         |
| Temperature-rise test   | Test passed                         |
| Conductor cross section short circuit testing                                   | 6 mm <sup>2</sup>                   |
| Short-time current  | 0.72 A                              |
| Conductor cross section short circuit testing                                   | 10 mm <sup>2</sup>                  |
| Short-time current  | 1.2 kA                              |
| Short circuit stability result  | Test passed                         |

## Feed-through terminal block - USSTD 6 - 3070325

### Technical data

#### General

|   |   |
|---|---|
| Proof of thermal characteristics (needle flame) effective duration    | 30 s  |
| Result of thermal test  | Test passed   |
| Test specification, oscillation, broadband noise                      | DIN EN 50155 (VDE 0115-200):2008-03                 |
| Test spectrum   | Service life test category 1, class B, body mounted |
| Test frequency  | $f_1 = 5 \text{ Hz}$ to $f_2 = 150 \text{ Hz}$      |
| ASD level   | 0.02 g <sup>2</sup> /Hz                             |
| Acceleration  | 0.8 g   |
| Test duration per axis  | 5 h   |
| Test directions   | X-, Y- and Z-axis                                   |
| Oscillation, broadband noise test result                              | Test passed   |
| Test specification, shock test  | DIN EN 50155 (VDE 0115-200):2008-03                 |
| Shock form  | Half-sine   |
| Acceleration  | 5 g   |
| Shock duration  | 30 ms   |
| Number of shocks per direction  | 3   |
| Test directions   | X-, Y- and Z-axis (pos. and neg.)                   |
| Shock test result   | Test passed   |
| Temperature index, insulating material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C  |

#### Dimensions

|                  |         |
|------------------|---------|
| Width            | 8.2 mm  |
| Length           | 82 mm   |
| Height NS 35/7,5 | 52 mm   |
| Height NS 35/15  | 59.5 mm |
| Height NS 32     | 57 mm   |

#### Connection data

|  |                      |
|--|----------------------|
| Conductor cross section solid min.   | 0.2 mm <sup>2</sup>  |
| Conductor cross section solid max.   | 10 mm <sup>2</sup>   |
| Conductor cross section AWG/kcmil min.                                     | 24                   |
| Conductor cross section AWG/kcmil max                                      | 8                    |
| Conductor cross section stranded min.                                      | 0.2 mm <sup>2</sup>  |
| Conductor cross section stranded max.                                      | 6 mm <sup>2</sup>    |
| Min. AWG conductor cross section, stranded                                 | 24                   |
| Max. AWG conductor cross section, stranded                                 | 10                   |
| Conductor cross section stranded, with ferrule without plastic sleeve min. | 0.25 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule without plastic sleeve max. | 6 mm <sup>2</sup>    |
| Conductor cross section stranded, with ferrule with plastic sleeve min.    | 0.25 mm <sup>2</sup> |

## Feed-through terminal block - USSTD 6 - 3070325

### Technical data

#### Connection data

|   |                                      |
|---|--------------------------------------|
| Conductor cross section stranded, with ferrule with plastic sleeve max.                 | 6 mm <sup>2</sup>                    |
| 2 conductors with same cross section, solid min.  | 0.2 mm <sup>2</sup>                  |
| 2 conductors with same cross section, solid max.  | 2.5 mm <sup>2</sup>                  |
| 2 conductors with same cross section, stranded min.                                     | 0.2 mm <sup>2</sup>                  |
| 2 conductors with same cross section, stranded max.                                     | 2.5 mm <sup>2</sup>                  |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm <sup>2</sup>                  |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 4 mm <sup>2</sup>                    |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.   | 0.25 mm <sup>2</sup>                 |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.   | 1.5 mm <sup>2</sup>                  |
| Connection method   | Screw connection with spring support |
| Stripping length  | 12 mm                                |
| Internal cylindrical gage   | A5                                   |
| Screw thread  | M4                                   |
| Tightening torque, min  | 1.5 Nm                               |
| Tightening torque max   | 1.8 Nm                               |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141120 |
| eCl@ss 4.1 | 27141120 |
| eCl@ss 5.0 | 27141120 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27141120 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC000897 |
| ETIM 5.0 | EC000897 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |

# Feed-through terminal block - USSTD 6 - 3070325

## Classifications

### UNSPSC

|              |          |
|--------------|----------|
| UNSPSC 11    | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2  | 39121410 |

## Approvals

### Approvals

#### Approvals

UL Recognized / cUL Recognized / cULus Recognized

#### Ex Approvals

#### Approvals submitted

## Approval details

|                                |       |       |       |
|--------------------------------|-------|-------|-------|
| UL Recognized                  |       |       |       |
|                                | B     | C     | D     |
| mm <sup>2</sup> /AWG/kcmil     | 24-10 | 24-10 | 24-10 |
| Nominal current I <sub>N</sub> | 30 A  | 30 A  | 5 A   |
| Nominal voltage U <sub>N</sub> | 300 V | 300 V | 600 V |

|                                |       |       |       |
|--------------------------------|-------|-------|-------|
| cUL Recognized                 |       |       |       |
|                                | B     | C     | D     |
| mm <sup>2</sup> /AWG/kcmil     | 24-10 | 24-10 | 24-10 |
| Nominal current I <sub>N</sub> | 30 A  | 30 A  | 5 A   |
| Nominal voltage U <sub>N</sub> | 300 V | 300 V | 600 V |

|                  |  |  |  |
|------------------|--|--|--|
| cULus Recognized |  |  |  |
|------------------|--|--|--|

## Feed-through terminal block - USSTD 6 - 3070325

### Accessories

#### Accessories

#### Bridge

Fixed bridge - FBRI 10-8 N - 2772080



Fixed bridge, Number of positions: 10, Color: silver

---

### Connector

Cable lug - C-BCI 1,5/2,8 - 3240015



Flat pin cable lug, red, 0.5 - 1.5 mm<sup>2</sup>,

---

Cable lug - C-BCI 1,5/4,6 - 3240568



Flat pin cable lug, red, 0.5 - 1.5 mm<sup>2</sup>,

---

Cable lug - C-BCI 2,5/2,8 - 3240046



Flat pin cable lug, blue, 1.5 - 2.5 mm<sup>2</sup>,

## Feed-through terminal block - USSTD 6 - 3070325

### Accessories

Cable lug - C-BCI 2,5/4,6 - 3240569



Flat pin cable lug, blue, 1.5 - 2.5 mm<sup>2</sup>,

---

Cable lug - C-BCI 6/2,8 SO - 3240057



Flat pin cable lug, with tab, soldered neck, yellow, 4 - 6 mm<sup>2</sup>, pin width 2.8 mm, easy conductor entry with Easy-Entry, also for vertical compression with CRIMPFOX-RCI 6

---

Cable lug - C-BCI 6/4,6 SO - 3240067



Flat pin cable lug, with tab, soldered neck, yellow, 4 - 6 mm<sup>2</sup>, pin width 4.6 mm, easy conductor entry with Easy-Entry, also for vertical compression with CRIMPFOX-RCI 6

---

### Crimping tool

Crimping pliers - CRIMPFOX-RCI 6 - 1212057



Crimping pliers, for insulated cable lugs, 0.75 - 6.0 mm<sup>2</sup> (red, blue, yellow), oval crimp, symmetrical

---

### End block

End clamp - CLIPFIX 35 - 3022218



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray

## Feed-through terminal block - USSTD 6 - 3070325

### Accessories

---

#### End clamp - CLIPFIX 35-5 - 3022276



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

---

#### End clamp - E/NS 35 N - 0800886



End clamp, width: 9.5 mm, color: gray

---

#### End clamp - E/UK - 1201442



End clamp, for assembly on NS 32 or NS 35/7.5 DIN rail

---

#### End clamp - E/UK 1 - 1201413



End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray

---

#### End cover

##### End cover - D-USST 6-T - 3070367



End cover, Length: 82 mm, Width: 2.2 mm, Color: gray

---



## Feed-through terminal block - USSTD 6 - 3070325

### Accessories

#### Labeled terminal marker

Zack marker strip - ZB 8 CUS - 0825011



Zack marker strip, Can be ordered: Strip, white, Labeled according to customer specifications, Mounting type: Snap into tall marker groove, For terminal block width: 8.2 mm, Lettering field: 10.5 x 8.15 mm

---

Marker for terminal blocks - UC-TM 8 CUS - 0824597



Marker for terminal blocks, Can be ordered: By sheet, white, Labeled according to customer specifications, Mounting type: Snap into tall marker groove, For terminal block width: 8.2 mm, Lettering field: 7.6 x 10.5 mm

---

Marker for terminal blocks - UCT-TM 8 CUS - 0829616



Marker for terminal blocks, Can be ordered: By sheet, white, Labeled according to customer specifications, Mounting type: Snap into tall marker groove, For terminal block width: 8.2 mm, Lettering field: 7.6 x 10.5 mm

---

### Mounting rail

DIN rail - NS 32 PERF 2000MM - 1201002



G-profile DIN rail, material: Steel, perforated, height 15 mm, width 32 mm, length 2 m

---

DIN rail - NS 32 UNPERF 2000MM - 1201015



G-profile DIN rail, material: Steel, unperforated, height 15 mm, width 32 mm, length 2 m

## Feed-through terminal block - USSTD 6 - 3070325

### Accessories

---

DIN rail perforated - NS 35/ 7,5 PERF 2000MM - 0801733



DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 7.5 mm, width 35 mm, length: 2000 mm

---

DIN rail - NS 35/ 7,5 UNPERF 2000MM - 0801681



DIN rail, material: Steel, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail - NS 35/ 7,5 WH PERF 2000MM - 1204119



DIN rail 35 mm (NS 35)

---

DIN rail - NS 35/ 7,5 WH UNPERF 2000MM - 1204122



DIN rail 35 mm (NS 35)

---

DIN rail, unperforated - NS 35/ 7,5 AL UNPERF 2000MM - 0801704



DIN rail, unperforated, Width: 35 mm, Height: 7.5 mm, Length: 2000 mm, Color: silver

---

## Feed-through terminal block - USSTD 6 - 3070325

### Accessories

DIN rail - NS 35/ 7,5 ZN PERF 2000MM - 1206421



DIN rail, material: Galvanized, perforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail - NS 35/ 7,5 ZN UNPERF 2000MM - 1206434



DIN rail, material: Galvanized, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail - NS 35/ 7,5 CU UNPERF 2000MM - 0801762



DIN rail, material: Copper, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

End cap - NS 35/ 7,5 CAP - 1206560

DIN rail end piece, for DIN rail NS 35/7.5

---

DIN rail perforated - NS 35/15 PERF 2000MM - 1201730



DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 15 mm, width 35 mm, length: 2000 mm

---

## Feed-through terminal block - USSTD 6 - 3070325

### Accessories

DIN rail - NS 35/15 UNPERF 2000MM - 1201714



DIN rail, material: Steel, unperforated, height 15 mm, width 35 mm, length: 2 m

---

DIN rail - NS 35/15 WH PERF 2000MM - 0806602



DIN rail 35 mm (NS 35)

---

DIN rail - NS 35/15 WH UNPERF 2000MM - 1204135



DIN rail 35 mm (NS 35)

---

DIN rail, unperforated - NS 35/15 AL UNPERF 2000MM - 1201756



DIN rail, deep drawn, high profile, unperforated, 1.5 mm thick, material: aluminum, height 15 mm, width 35 mm, length 2000 mm

---

DIN rail - NS 35/15 ZN PERF 2000MM - 1206599



DIN rail, material: Galvanized, perforated, height 15 mm, width 35 mm, length: 2 m

---

## Feed-through terminal block - USSTD 6 - 3070325

### Accessories

DIN rail - NS 35/15 ZN UNPERF 2000MM - 1206586



DIN rail, material: Galvanized, unperforated, height 15 mm, width 35 mm, length: 2 m

---

DIN rail - NS 35/15 CU UNPERF 2000MM - 1201895



DIN rail, material: Copper, unperforated, 1.5 mm thick, height 15 mm, width 35 mm, length: 2 m

---

End cap - NS 35/15 CAP - 1206573



DIN rail end piece, for DIN rail NS 35/15

---

DIN rail - NS 35/15-2,3 UNPERF 2000MM - 1201798



DIN rail, material: Steel, unperforated, 2.3 mm thick, height 15 mm, width 35 mm, length: 2 m

---

### Partition plate

Partition plate - ATP-URTK/SP - 0311139



Partition plate, Length: 99 mm, Width: 2 mm, Height: 64 mm, Color: gray

---

## Feed-through terminal block - USSTD 6 - 3070325

### Accessories

#### Screwdriver tools

Screwdriver - SZS 1,0X4,0 VDE - 1205066



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 4.0 x 100 mm, 2-component grip, with non-slip grip

---

Screwdriver - SZS 0,6X3,5 - 1205053



Actuation tool, for ST terminal blocks, insulated, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

---

#### Short-circuit connector

Short-circuit connector - KSS 8 - 0311540



Short-circuit connector, Number of positions: 2, Color: black

---

Short-circuit connector - KSS 4- 8 - 0309549



Short-circuit connector, Number of positions: 4, Color: black

---

#### Terminal marking

## Feed-through terminal block - USSTD 6 - 3070325

### Accessories

Zack marker strip - ZB 8:UNBEDRUCKT - 1052002



Zack marker strip, Strip, white, Unlabeled, Can be labeled with: Plotter, Mounting type: Snap into tall marker groove, For terminal block width: 8.2 mm, Lettering field: 10.5 x 8.15 mm

Marker for terminal blocks - UC-TM 8 - 0818072



Marker for terminal blocks, Sheet, white, Unlabeled, Can be labeled with: BLUEMARK CLED, BLUEMARK LED, Plotter, Mounting type: Snap into tall marker groove, For terminal block width: 8.2 mm, Lettering field: 7.6 x 10.5 mm

Marker for terminal blocks - UCT-TM 8 - 0828740



Marker for terminal blocks, Sheet, white, Unlabeled, Can be labeled with: THERMOMARK CARD PLUS, THERMOMARK CARD, BLUEMARK CLED, BLUEMARK LED, Mounting type: Snap into tall marker groove, For terminal block width: 8.2 mm, Lettering field: 7.6 x 10.5 mm

### Test socket

Female test connector - PSBJ-URTK 6 FARBLOS - 3026450



Female test connector, Color: transparent

Female test connector - PSBJ-URTK 6 RD - 3026719



Female test connector, Color: red

## Feed-through terminal block - USSTD 6 - 3070325

### Accessories

Female test connector - PSBJ-URTK 6 BU - 3026434



Female test connector, Color: blue

---

Female test connector - PSBJ-URTK 6 YE - 3026405



Female test connector, Color: yellow

---

Female test connector - PSBJ-URTK 6 GN - 3026418



Female test connector, Color: green

---

Female test connector - PSBJ-URTK 6 VT - 3026421



Female test connector, Color: violet

---

Female test connector - PSBJ-URTK 6 GY - 3026612



Female test connector, Color: gray

---



## Feed-through terminal block - USSTD 6 - 3070325

### Accessories

Female test connector - PSBJ-URTK 6 BK - 3026447



Female test connector, Color: black

---

Female test connector - PSBJ-URTK 6 BN - 3026971



Female test connector, Color: brown

---

### Drawings

Circuit diagram

