





REV.	DESCRIPTION	DATE
A	RELEASE	2018.07.03

RoHS

NOTES:
 Insulator Material: Nylon-6T, UL 94V-0
 Contact Plating: Flash Gold
 Contact Material: Brass

Current Rating : 1A AC,DC
 Contact Resistance: 20mΩ Max.
 Dielectric Withstanding: AC 500V
 Insulator Resistance: 1000MΩ Min.
 Operating Temp.: -40°C~+105°C



P.C.B LAYOUT

NUMBER OF POSITIONS	DIMENSIONS	
	A	B
06	2.54	18.31
08	3.81	19.58
10	5.08	20.85
12	6.35	22.12
14	7.62	23.39
16	8.89	24.66
18	10.16	25.93
20	11.42	27.20
24	13.97	29.74
26	15.24	31.01
30	17.78	33.55
34	20.32	36.09
40	24.13	39.90
50	30.48	46.25
60	36.83	52.60
64	39.37	55.14

Cnc Tech,LLC

3210-XX-003-12-00

UNLESS TOLERANCE		DRAW BY	
GENERAL	ANGLE	DESIGN BY	
X ± 0.30	X° ± 3.0'	CHECK BY	
.X ± 0.20	.X° ± 2.0'	APPROVE BY	
.XX ± 0.15	.XX° ± 1.0'		
.XXX ± 0.08	.XXX° ± 0.5'		

SCALE	SHEET	UNIT
1:1	1/1	MM

DRW NO.:

REV. A