


SERIES

4426R
4426

RoHS
Compliant
Traditional
First Quality

Air Core Inductors

| DASH NUMBER* | TURNS (Ref.) | INDUCTANCE (nH) | TEST FREQUENCY (MHz) | Q Min. | CURRENT RATING MAXIMUM (Amps) | SRF GHz, Min. | SIZE CODE |
|--------------|--------------|-----------------|----------------------|--------|-------------------------------|---------------|-----------|
|--------------|--------------|-----------------|----------------------|--------|-------------------------------|---------------|-----------|




| SERIES 4426 | | | | | | | |
|-------------|----|---------|-----|-----|-----|-----|---|
| -1 | 1 | 2.5±10% | 145 | 150 | >3 | 3.0 | A |
| -2 | 2 | 5.0±10% | 140 | 150 | >3 | 3.0 | A |
| -3 | 3 | 8.0±5% | 140 | 150 | >3 | 3.0 | A |
| -4 | 4 | 12.5±5% | 137 | 150 | >3 | 3.0 | A |
| -5 | 5 | 18.5±5% | 132 | 150 | >3 | 3.0 | A |
| -6 | 6 | 17.5±5% | 100 | 150 | >3 | 3.0 | B |
| -7 | 7 | 22.0±5% | 102 | 150 | >3 | 3.0 | B |
| -8 | 8 | 28.0±5% | 105 | 150 | 2.6 | 3.0 | B |
| -9 | 9 | 35.5±5% | 112 | 150 | 1.8 | 3.0 | B |
| -10 | 11 | 43.0±5% | 106 | 150 | 1.5 | 3.0 | B |

*Complete part # must include series # PLUS the dash #
For surface finish information, refer to www.delevanfinishes.com

Actual Size

| | Size A in. | Size A mm | Size B in. | Size B mm |
|-------|------------|-----------|------------|-----------|
| A Max | 0.120 | 3.05 | 0.120 | 3.05 |
| B Max | 0.125 | 3.18 | 0.125 | 3.18 |
| C Max | 0.145 | 3.68 | 0.270 | 6.86r |
| D | 0.115±.010 | 2.92±.25 | 0.230±.010 | 5.84±.25 |
| E | 0.05±.015 | 1.27±.38 | 0.05±.015 | 1.27±.38 |
| F | 0.165 | 4.19 | 0.285 | 7.23 |
| G | 0.110 | 2.79 | 0.110 | 2.79 |
| H | 0.130 | 3.30 | 0.130 | 3.30 |
| I | 0.050 | 1.27 | 0.050 | 1.27 |
| J | 0.065 | 1.65 | 0.185 | 4.69 |



High Q, wire wound air cores Designed to operate over a wide frequency range. Standard flat cap top is suitable for automatic placement.

***Ordering** Suffix the dash number with RC to order optional water dissolvable flat top cap for applications requiring hand adjustment. The cap allows the part to be pick and placed onto the PCB, and will dissolve in almost all board cleaning solvents, leaving no residue. Suffix the dash number with NC to order option with no cap, for manual placement.

Operating Temperature Range -55°C to +125°C

Packaging Tape & reel

Size A, (12mm): 7" reel, 650 pieces max.; 13" reel, 2500 pieces max.;

Size B, (16mm): 7" reel, 400 pieces max.; 13" reel, 1400 pieces max.