

1 | 2

3

4

PRODUCT NO.	DIM "X"		
	4.25±0.1	3.5±0.1	5.0±0.1
73590-001	OTHERS	36,67	1,17,34,35,51,68
73590-001LF	OTHERS	36,67	1,17,34,35,51,68

NOTES

① MATERIAL
 HOUSING : LCP UL94V-0 BLACK.
 PIN : PHOSPHOR BRONZE.

② FINISH - PIN
 UNDER PLATING : 0.5um Ni.
 CONTACT AREA : 0.1um GOLD OVER
 0.5um Pd-Ni
 SOLDER TAIL : 2.5um Sn-Pb.
 : 2.5um PURE Sn (FOR -001LF)

3 RECOMMENDED SCREW TORQUE 1.0 TO 1.5 MAX in-lbs. (1.2-1.7 cm-kgs).
 RECOMMENDED HOLD-DOWN: 2mm SCREWS (95121) AND HEX NUTS (92869-001).

4 IF LEAD FREE P/N.THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.00MM MINIMUM THICK CIRCUIT BOARD.
 5 IF LEAD FREE P/N.THE PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008
 6 LEAD FREE P/N PACKAGING MEETS GS-14-920 SPECIFICATION

Tous droits strictement reserves. Reproduction ou communication a des tiers interdite sous quelque forme que ce soit sans autorisation ecrite du proprietaire. Propriete de ©BERG ELECTRONICS. Droits de reproduction BERG ELECTRONICS INC.

All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of ©BERG ELECTRONICS Copyright BERG ELECTRONICS INC.

mat'l. code				tolerances unless otherwise specified			CUSTOMER COPY		 www.fciconnect.com			
ltr	ecn no	dr	date	linear	.X ±.3			projection	title			
A	V70945	RHG	7/22/97		.XX ±.13				68 POS. EJECT			
B	N05-0196	WB	07/05/05	angles	.XXX ±.051			 mm	HEADER ASSY			
					0° ±2°				product family PCMCIA			
				dr	R.GRAPE	7/22/97	scale	A4	73590	code		
				engr	D BRANN	7/22/97				size	dwg no	-
				chr	D BRANN	7/22/97				1:1	sheet	1 of 1
				appd	D BRANN	7/22/97						
sheet index	revision sheet	B	1									

form no. 7530-001-103

1 | 2

3

4

PDM: Rev:B

STATUS Released
 cage code 22526
 Printed: Oct 12, 2010