

Number of contacts	64	78.74	81.58	86.08	80.01	81.28	0.89
	60	73.66	76.50	81.00	74.93	76.20	0.89
	50	60.96	63.80	68.30	62.23	63.50	0.89
	40	48.26	51.10	55.60	49.53	50.80	0.89
	A ±0.05	B ^{+0.1} ₀	C ±0.1	E ±0.2	L ±0.32	M ±0.13	
Dimensions							

ORDERING INFORMATION


SERIES: 8613
 NO. OF CONTACTS :- 0403030355
 40,50,60,64
 3 - FEMALE WITH CENTRAL POLARISING
 0 - WITHOUT STRAIN RELIEF CLAMP
 1 - WITH STRAIN RELIEF CLAMP
 TYPE OF TERMINATION
 30 - INSULATION DISPLACEMENT 28 GAUGE

SPECIAL CODE
 000 - TIN LEAD VERSION
 E1LF - LEAD FREE VERSION
 LONGITUDINAL PITCH
 5 - 2.54 mm
 PERFORMANCE CLASS
 4 - DIN 41651 CLASS 3
 5 - DIN 41651 CLASS 2
 6 - DIN 41651 CLASS 1
 8 - AS PER JSS 50810
 INSULATOR MATERIAL
 3 - PBT GREY

TECHNICAL SPECIFICATION

HOUSING MATERIAL : THERMOPLASTIC POLYESTER UL 94V0; GREY
 CONTACT MATERIAL : COPPER ALLOY
 PLATING : ACTIVE ZONE - GOLD OVER NICKEL
 : TERMINATION ZONE - SnPb OVER Ni FOR TIN LEAD VERSION.
 : - Sn (MATTE TIN) OVER Ni FOR LEAD FREE VERSION.

CURRENT RATING : 1.5A AT 20°C
 INSULATION RESISTANCE AT 500Vdc : ≥5000 MΩ at 100V
 CONTACT RESISTANCE : ≤20 mΩ
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 Vrms
 OPERATING TEMPERATURE : -55°C TO +125°C
 REFERENCE SPECIFICATION : IEC 603-13 / DIN 41651



NOTES:-

- THE "LF" PRODUCTS MEET EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008
- LEAD FREE OR RoHS DIRECTIVE LABELING TO BE PROVIDED AS PER GS-14-920 FOR RoHS COMPATIBLE VERSION.

mat'l. code		surface		tolerance		projection		product family	
-		ISO 1302 ✓		ISO 406 ISO 1101				8613	
litr		ecn no		dr		date		title	
A		-		YMP		1998-12-06		FEMALE CONNECTOR	
B		-		MINI		2002-04-22		FLAT CABLE 8613 SERIES	
C		I06-0066		MINI		2006-06-01		scale -	
D		I06-0173		MINI		2006-09-15		dwg no	
				enr		P.S.JOHNS		sheet 1 of 1 size	
				chr		RAKHEE GEORGE		A3	
				appd		RAKHEE GEORGE		type Product Customer Drawing	
sheet index		revision sheet		D					
		1							