



Specification:

1. Electrical Char
Insulation Resistance: 500MΩ min. 500V DC for 1 minute
Contact Resistance: 30mΩ max.
Rating Current: 1.5A max.
Rating Voltage: 150V AC
2. Physical Char
Housing: PBT Glass filled (UL 94V-0) Color: Black
Soldering Temperature: 235°C for 5 sec.
Spring Wire: 0.35mm thickness Phosphor Bronze
6u" Gold on contact area over 50u" Nickel
Temperature Range: -40°C to +85°C
Durability: 750 mating cycles min.
3. Packing: Tray

RoHS compliant
Unit:mm

Scale	Free		
TOLERANCE			
.XX	±0.25		
.XXX	±0.13		
.XXXX	±0.05		
DIM	TOL		
		① Update the tolerance & Rating Voltage	12.07.2018
		① Drawn	21.07.2016
Angle	+0°30'	Id.	Modification

Date	Name	Customer-No.
21.07.2017	Winnie	
12.07.2018	Winnie	

ASSMANN WSW-No. A-2004-2-4-LP/S-R

ASSMANN WSW components

ASS 7322 CO rev01

ASSMANN WSW components

1	2	3	4	5	6	7	A
1	2	3	4	5	6	7	B
1	2	3	4	5	6	7	C
1	2	3	4	5	6	7	D
1	2	3	4	5	6	7	E
1	2	3	4	5	6	7	F
1	2	3	4	5	6	7	G
1	2	3	4	5	6	7	H