

1

2

3

4

5

6

7

A

A

Panel Thickness
Screw L=5.0 For Panel Thickness Under 1.2mm
Screw L=6.0 For Panel Thickness Between 1.2-2.0mm

C

Recommended Panel Cut-Out

D

D

With Liquid Glue

NOTES:

MATERIAL

1. Insulator Material: Black, NYLON+G/F
2. Contact Material: Copper Alloy
3. Plating: Gold Plating
4. Waterproof Rate: IP67
5. Do Mating Test After Glued
6. LOGO

E

E

15 Pin Female Connector
PCB Pin Layout
Scale 2:1

F

F

RoHS compliant

G

G

| | | | | | | | | |
|-----------|-------|-----|--------------|------------|------|----------|------------|---|
| Scale | 1:1 | | | | | Date | Name | Customer-No. |
| TOLERANCE | | | | | | Drawn | 24.12.2008 | JACK |
| X.X | ±0.25 | | | | | Approved | 24.12.2008 | Hellwig |
| X.XX | ±0.10 | | | | | | | |
| X.XXX | ±0.05 | | | | | | | |
| DIM | TOL | | | | | | | Drawing-No. |
| ANGLE | ±1° | | | | | | | ASSMANN WSW-No. A-DF 15 PP-WP |
| X.X° | ±X° | ① | Drawn | 24.12.2008 | JACK | | | ASS 3254 CO rev01 |
| Angle | TOL | Id. | Modification | Date | Name | | | Replace |

H

H

1

2

3

4

5

6

7