



Material
 Item @ Clamp : Brass(CuZn) Ni plated
 Item Ⓛ Terminal screw: Steel Zinc plating "I" slot type
 Item ⓐ Female contact : PhBz(CuZn)Tin plated
 Item Ⓞ Terminal housing: Thermoplastic (UL94V-0)
 Green(RAL6018/T)

Electrical cULus
 Voltage rating: 300V
 Current rating: 10A
 Wire range:
 Solid wire(AWG): 16-28
 Stranded wire(AWG): 16-28
 Torque(Lb-In): 1.7
 Screw: M2
 Wire strip length: 5-6mm
 Withstanding Voltage: 1.6KV
 Ⓞ Operating temperature: -40°C to +115°C
 Safety approval: cULus

| DIMENSION | |
|-----------|-----------|
| A | Nx3.5 |
| B | (N-1)x3.5 |

N=Number of poles

| Poles | Tolerance | |
|---------|-----------|-------|
| | DIM A | DIM B |
| 4p-6p | ±0.20 | ±0.15 |
| 7p-12p | ±0.25 | ±0.20 |
| 13p-24p | ±0.30 | ±0.25 |

RoHS compliant
 Unit: mm

 File No.: E349947

| Scale | Free TOLERANCE | Free TOL | Id. | Modification | Date | Name |
|-------|----------------|----------|-----|----------------------------------|------------|---------|
| X. | ±0.50 | | ② | Update | 20.04.2010 | Alex |
| X.X | ±0.30 | | ① | Drawn | 30.11.2006 | Hellwig |
| X.XX | ±0.10 | | ③ | Update to new drawing and add UL | 25.03.2016 | Amy |
| DIM | TOL | | | | | |
| X.° | ±1° | | | | | |
| Angle | TOL | | | | | |

| Date | Name | Date | Name |
|------------|---------|------------|------|
| 30.11.2006 | Hellwig | 25.03.2016 | Amy |
| 20.04.2010 | Alex | | |

| | | | | |
|--------------|-----------------|-------------|---------|-------|
| Customer-No. | ASSMANN WSW-No. | Drawing-No. | Replace | Sheet |
| | A-TB350-THXX | ASS 1150 CO | rev03 | |

ASSMANN
 WSW components

1 2 3 4 5 6 7

H G F E D C B A