



Material

- Item a Clamp: Brass (CuZn), Ni plated
- Item b Terminal screw: Steel Zinc plating "-" slot type
- Item c Female contact : PhBz Tin plated
- Item d Terminal (housing): Thermoplastic (UL94V-0) Green(RAL6018/T)

Electrical cULus

- Voltage rating: 300VAC
- Current rating: 10A
- Wire range:
- Solid wire(AWG): 16-28
- Stranded wire(AWG): 16-28
- Torque(Lb-in): 1,7
- Screw: M2
- Wire strip length: 5-6mm
- Withstanding Voltage: 1,6KV
- Operating temperature: -40°C to +115°C
- Safety Approval: **cULus**

DIMENSION

L	Nx3.5
P	(N-1)x3.5

N=Number of poles

Poles	Tolerance	
	DIM L	DIM P
2p-6p	±0.15	±0.15
7p-12p	±0.20	±0.20
13p-18p	±0.25	±0.25
19p-24p	±0.30	±0.30

Customer-No. ASSMANN WSW-No. **A-TB350-TTXX**

Drawing-No. **ASS 2251 CO**

Replace **rev03** Sheet

RoHS compliant
Unit: mm



Scale	Free	Id.	Modification	Date	Name
TOLERANCE					
X.	±0.50				
X.X	±0.30				
X.XX	±0.10	③	Add UL	18.04.2016	Amy
DIM	TOL	②	Update	20.04.2010	Alex
X.°	±1°	①	Drawn	14.06.2007	Hellwig
Angle	TOL				

Date	Name
14.06.2007	Alex
18.04.2016	Amy



1	2	3	4	5	6	7	A
							B
							C
							D
							E
							F
							G
							H