



SUMMARY

Wires

 Low
 0

 High
 0

 Coax
 0

 Triax
 0

Quad 0 **Fiber** 0

Fluidic 0

Series 2M

Termination type No contacts / Accessory

IP rating 50

Cable Ø 0.00 - 0.00 mm

Matching parts

Status active

Alternative part



Image is for illustrative purpose only

Download

Request a quote

Catalog

TECHNICAL DETAILS

Mechanics

Shell Style/Model BME*: Blanking cap for fixed receptacle(knurled grip)

Keying

Housing Material Environment friendly aluminium (nickel plated, anthracite color) shell and nut, other pieces

bronze/brass

Cable Fixing : 0 - 0 mm

Variant

Weight 5.77 g

Performance

Configuration

Insulator

Rated Current

Specifications

Contact LEMO for performance details.

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Others

Humidity (max): <=95% [at 60 deg C /140 F]

Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [6 ms]


Operating temperature: -55°C/ +200°C Climatical Category: 15/200/21 (Al. shell) Lighting strike EIA 364-75 10K amps - 6 times

EMI Shielding EIA 364-66A - 1Ghz-80 dB,3GHz-70 dB,6GHz- 58dB

IP Rating: 50

DRAWINGS

Draws





Dimensions

	А	С	L	N	Р	Х
mm.	17.6	17.2	23.4	85	3.9	6
in.	0,69	0,68	0,92	3,35	0,15	0,24

RECOMMENDED BY LEMO

Tools

None

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

121 221 131 221	-	
151 221		
161 221		

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.