



www.lemo.com

SUMMARY

Wires

 Low
 0

 High
 0

 Coax
 0

Triax 0

Quad 0 Fiber 0

Fluidic 0

Series 0V

Termination type No contacts / Accessory

IP rating 68

Cable Ø 0.00 - 0.00 mm

Matching parts

Status active

Alternative part



Image is for illustrative purpose only

Download

Request a quote

Catalog

TECHNICAL DETAILS

Mechanics

Shell Style/Model BRE*: Cap for receptacle

Keying No keying

Housing Material Brass (nickel plated) shell, collet nut, latch sleeve and mid pieces

Cable Fixing : 0 - 0 mm

Variant

Weight 12.58 g

Performance

Configuration

Insulator

Rated Current


Others

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Pressure: 30 bars IP Rating: 68

DRAWINGS

Draws



No keying

Dimensions

	А	L	N	S1
mm.	17.2	13.7	85	16
in.	0,68	0,54	3,35	0,63

RECOMMENDED BY LEMO

Tools

None

Cables

121 221		
131 221		
151 221		
161 221		

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.