

SUMMARY

Wires

Low	4
High	0
Coax	0
Triax	0
Quad	0
Fiber	0
Fluidic	0



Image is for illustrative purpose only

Download

[Request a quote](#)

[Catalog](#)

Series	C
Termination type	Male crimp
IP rating	50
Cable Ø	7.30 - 9.20 mm
Matching parts	CLB.M04.GLLG
Status	active
Alternative part	

TECHNICAL DETAILS

Mechanics

Shell Style/Model	CA*: Straight plug with cable collet
Keying	3 keys (alpha=0, gamma=60; Plug: male contacts; Receptacle: female contacts)
Housing Material	PSU (Polysulfone), gray
Cable Fixing	∅ 7.3 - 9.2 mm
Variant	
Weight	8.82 g

Performance

Configuration	2P.M04 : 4 Low V.
Insulator	
Rated Current	15 Amps

Specifications

Test voltage (kV rms) Contact-contact:	1.85
Air clearance min. (mm) or Creepage distance min. (mm):	1.8

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Others

F ret (min): 150 N


F ret (max): 250 N

Steam sterilization: 20 times (with potting on rear connection)

IP Rating: 50

DRAWINGS

Draws



Dimensions

	A	L
mm.	18	53
in.	0,71	2,09

RECOMMENDED BY LEMO

Tools

Crimp Tool: DPC.91.701.V

Crimp settings: AWG/Selector = 18-20/8-7

Positionner: DCE.91.132.BVC

Extractor: DCF.91.131.2LT

Replacement contact: FGG.2B.565.ZZC

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.