

FFA.1S.650.CTAC62Z

an con

SUMMARY

......

# Wires			
Low	0		
High	0		
Coax	0		Image is for illustrative purpose only
Triax	1	Download	
Quad	0	Request a quote	
Fiber	0	Catalog	
Fluidic	0	<u>v</u>	
Series	1S		
Termination type	Male solder		
IP rating	50		
Cable Ø	5.20 - 6.20 mm		
Matching parts	ERA.1S.650.CLL		
Status	active		
Alternative part			

TECHNICAL DETAILS

Mechanics

Shell Style/Model	FFA*: Straight plug, cable collet and nut for fitting a bend relief		
Keying	Circular (can rotate), plug has male contact(s)		
Housing Material	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces		
Cable Fixing	C62: 5.2 - 6.2 mm		
Variant	Z : Nut for fitting a bend relief		
Weight	19.08 g		

Performance

Configuration	1S.650 : 1 Triax (50 Ohm)		
Insulator	T: PTFE		
Rated Current	6 Amps		

Specifications

Contact Type: Triaxial 50 Ohm (Solder) Max. Matings: 1000

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.


Contact Dia.: 0.9 mm (0.035in) Vtest: 1200 V (AC), 1700 V (DC) Impedance: 50 Ohm VSWR: 1.01 + 0.17 * f/GHz Cable type: RGT 178, RGT 174,Belden 9222

Others

Endurance (Shell): 5000 mating cycles Temp (min / max): -55°C / +250°C Humidity (max): <=95% [at 60 deg C /140 F] Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [6 ms] Salt Spray Corrosion: >144 hr Climatical Category: 50/175/21 Shielding (min): 75 dB (10 MHz) Shielding (min): 40 dB (1 GHz) IP Rating: 50

DRAWINGS

Draws





Dimensions

	А	L	Μ	S2
mm.	12	42.5	31.5	9
in.	0,47	1,67	1,24	0,35

RECOMMENDED BY LEMO

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Tools

Spanner wrench: DCD.1B.015.PA090

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.