

SUMMARY



Image is for illustrative purpose only

Wires

Low	0
High	1
Coax	0
Triax	0
Quad	0
Fiber	0
Fluidic	0

Download

[Request a quote](#)

[Catalog](#)

Series	1Y
Termination type	Female solder High-Voltage
IP rating	50
Cable Ø	4.20 - 5.20 mm
Matching parts	ERA.1Y.405.CTA
Status	active
Alternative part	

TECHNICAL DETAILS

Mechanics

Shell Style/Model	FFA*: Straight plug with cable collet
Keying	Circular (can rotate)
Housing Material	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
Cable Fixing	C52: 4.2 - 5.2 mm
Variant	
Weight	36.01 g

Performance

Configuration	
Insulator	T: PTFE
Rated Current	8 Amps

Specifications

Contact Type: Solder	
Test voltage (kV DC)	10.5
Test voltage (kV AC)	7.5

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.


Creepage dist. (mm): 16

Others

IP Rating: 50

DRAWINGS

Draws



Dimensions

	A	L	M	S1
mm.	13	67	30.5	9
in.	0,51	2,64	1,20	0,35

RECOMMENDED BY LEMO

Tools

None

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.