

SUMMARY

Wires

| | |
|---------|---|
| Low | 3 |
| High | 0 |
| Coax | 0 |
| Triax | 0 |
| Quad | 0 |
| Fiber | 0 |
| Fluidic | 0 |



Image is for illustrative purpose only

Download

[Request a quote](#)

[Catalog](#)

| | |
|------------------|----------------|
| Series | 2C |
| Termination type | Male solder |
| IP rating | 50 |
| Cable Ø | 2.70 - 3.10 mm |
| Matching parts | ERA.2C.303.CLL |
| Status | active |
| Alternative part | |

TECHNICAL DETAILS

Mechanics

| | |
|-------------------|---|
| Shell Style/Model | FFA*: Straight plug, cable collet |
| Keying | Hermaphroditic keying ("half moon" insert), plug has male pin 1 |
| Housing Material | Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces |
| Cable Fixing | C32: 2.7 - 3.1 mm |
| Variant | |
| Weight | 14.36 g |

Performance

| | |
|---------------|--|
| Configuration | 2C.303 : 3 Low Voltage |
| Insulator | L: PEEK (UL 94 / V-0/3.2, depends on material thickness) |
| Rated Current | 15 Amps |

Specifications

Contact Type: Solder
Vtest: 1500 V (AC), 2100 V (DC)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Others

Endurance (Shell): 500 mating cycles
IP Rating: 50

DRAWINGS

Draws



Dimensions

| | A | L |
|-----|------|------|
| mm. | 14 | 30 |
| in. | 0,55 | 1,18 |

RECOMMENDED BY LEMO


Tools

None

Cables

| | | | |
|--------------------|-----|-------|--|
| CMN.03.T28.031PGCE | PVC | GREY | |
| CMN.03.T28.031PGZE | | Grey | |
| CMN.03.T28.031PNCE | PVC | Black | |
| CMN.03.T28.031PNZE | | | |

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

| | | | |
|---------|-----|-------|---|
| 003 050 | PVC | Black |  |
| 003 081 | PVC | Black | |

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.