

## SUMMARY

### # Wires

|         |   |
|---------|---|
| Low     | 0 |
| High    | 0 |
| Coax    | 0 |
| Triax   | 1 |
| Quad    | 0 |
| Fiber   | 0 |
| Fluidic | 0 |



Image is for illustrative purpose only

### Download

[Request a quote](#)

[Catalog](#)

|                  |                |
|------------------|----------------|
| Series           | 00             |
| Termination type | Male solder    |
| IP rating        | 50             |
| Cable Ø          | 2.30 - 2.70 mm |
| Matching parts   | ERN.00.650.CLL |
| Status           | active         |
| Alternative part |                |

## TECHNICAL DETAILS

### Mechanics

|                   |  |
|-------------------|--|
| Shell Style/Model | FFC*: Straight plug with flats on latch sleeve and cable collet, black POM (Delrin®) outershell) |
| Keying            | Circular (can rotate)  |
| Housing Material  | Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces      |
| Cable Fixing      | C27: 2.3 - 2.7 mm  |
| Variant           | Z : Nut for fitting a bend relief  |
| Weight            | 4.08 g   |

### Performance

|               |  |
|---------------|--|
| Configuration | 0.65 : 1 Triax (50 Ohm)                                  |
| Insulator     | L: PEEK (UL 94 / V-0/3.2, depends on material thickness) |
| Rated Current | 3 Amps   |

### Specifications

Contact Type: Triaxial 50 Ohm (Solder)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Max. Matings: 1000  
Contact Dia.: 0.5 mm (0.02" in)  
Vtest: 1200 V (AC), 1700 V (DC)  
Impedance: 50 Ohm  
VSWR: 1.1 + 0.11 \* f/GHz


## Others

IP Rating: 50

---

# DRAWINGS

## Draws



## Dimensions

|     | A    | L    | M    |
|-----|------|------|------|
| mm. | 6.4  | 29.2 | 18   |
| in. | 0,25 | 1,15 | 0,71 |

---

# RECOMMENDED BY LEMO

## Tools

Spanner wrench: DCD.00.003.PA050

## Cables

*LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.*

*LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.*