

# FFE.00.250.CLAC22D

# SUMMARY

#### # Wires



Low	0		
High	0		
Coax	1		Image is for illustrative purpose only
Triax	0	Download	
Quad	0	Request a quote	
Fiber	0	Catalog	
Fluidic	0	<u></u>	
Series	00		
Termination type	Male solder		
IP rating	50		
Cable Ø	1.80 - 2.20 mm		
Matching parts	ERA.00.250.CTL		
Status	active		
Alternative part			

# **TECHNICAL DETAILS**

#### **Mechanics**

	Shell Style/Model	FFE*: Straight plug with front sealing ring, cable collet	
	Keying	Circular (can rotate)	
	Housing Material	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces	
	Cable Fixing	C22: 1.8 - 2.2 mm	
	Variant		
	Weight	4.78 g	
Ρ	erformance		
	Configuration	0.25 : 1 Coax (50 Ohm)	
	Insulator	L: PEEK (UL 94 / V-0/3.2, depends on material thickness)	
	Rated Current	4 Amps	

#### **Specifications**

Contact Type: Coaxial 50 Ohm (Solder) Max. Matings: 5000 Contact Dia.: 0.7 mm (0.028in)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Bucket Dia.: 0.6 mm (0.024in) Test voltage: 2.1 kV (rms) R (max): 6.1 mOhm Vtest: 2100 V (AC), 3000 V (DC)


Impedance: 50 Ohm VSWR: 1.09 + 0.11 \* f/GHz Cable type: RG 196 A/U - RG 178 B/U - LEMO Germany reference 178 190

#### Others

Endurance (Shell): 5000 mating cycles F ret (min): 100 N IP Rating: 50

### DRAWINGS

Draws



#### Dimensions

	А	L	Μ
mm.	7.4	33.5	25.5
in.	0,29	1,32	1,00

## **RECOMMENDED BY LEMO**

#### Tools

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

None

#### Cables

178 190	PTFE	Brown	
196 270	PTFE	White	
CCX.50.030.083.180B		White	
CCX.50.RG1.78BU18M	FEP	Brown	
CCX.50.RG1.78BU18M	PTFE	Brown	
CCX.50.RG1.96AU19B	PTFE	White	
CCX.50.RG1.96AU20B	PFA	White	

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.