

# FGG.0B.701.CJAD52

# SUMMARY

#### # Wires

Low	1
High	1
Coax	0
Triax	0
Quad	0
Fiber	0
Fluidic	0
Series	OB
Termination type	Male solder High-Voltage
IP rating	50
Cable Ø	4.30 - 5.20 mm
Matching parts	EGG.0B.701.CJL
<b>•</b>	
Status	active



Image is for illustrative purpose only

# Download

Request a quote Catalog

## **TECHNICAL DETAILS**

#### **Mechanics**

Shell Style/Model	FG*: Straight plug, cable collet
Keying	1 key (alpha=0, plug: male contacts, receptacle: female contacts)
Housing Material	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
Cable Fixing	D52: 4.3 - 5.2 mm
Variant	
Weight	8.31 g
Performance	
Configuration	0B.701 : 1 High V. 1 Low V.

Insulator	J: PEEK/PEEK		
Rated Current	7 Amps		

#### **Specifications**

Contact Type: Solder Test voltage HV Ue (kV dc) 8.3 Test voltage HV Ue (kV rms) 5.9

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.


Test voltage LV cont-shell(kV dc) 1.35 Test voltage LV cont-shell(kV rms) 0.95

#### Others

Endurance (Shell): 5000 Temp (min / max): -55°C / +250°C Humidity (max): <=95% [at 60 deg C /140 F] Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [ 6 ms] Salt Spray Corrosion: >1000 hr Climatical Category: 50/175/21 Shielding (min): 75 dB (10 MHz) Shielding (min): 40 dB (1 GHz) IP Rating: 50

### DRAWINGS

#### Draws



#### Dimensions

	А	L	Μ	S1	S2
mm.	9.5	36	26	8	7
in.	0,37	1,42	1,02	0,31	0,28

### **RECOMMENDED BY LEMO**

#### Tools

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

0°

Spanner wrench: DCD.0B.005.PA070 Caps: BFG.0B.100.PCSG

#### Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.