

www.lemo.com

FGG.1B.803.CLAD722

SUMMARY

Wires

 Low
 3

 High
 0

 Coax
 1

 Triax
 0

 Quad
 0

 Fiber
 0

 Fluidic
 0

Series 1B

Termination type Male solder Mixed coaxial /

IP rating 50

Cable Ø 6.30 - 7.20 mm

Matching parts EGG.1B.803.CLL2

Status active

Alternative part



Image is for illustrative purpose only

Download

Request a quote

Catalog

See video assembly instructions

TECHNICAL DETAILS

Mechanics

Shell Style/Model FG*: Straight plug, cable collet

Keying 1 key (alpha=0, plug: male contacts, receptacle: female contacts)

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Cable Fixing D72: 6.3 - 7.2 mm

Variant

Weight 15.71 g

Performance

Configuration

Insulator L: PEEK (UL 94 / V-0/3.2, depends on material thickness)

Rated Current 10 Amps

Specifications

Contact Type: Coaxial 50 Ohm (Solder) Type F

Test voltage (kV rms): 0.75 Test voltage (kV dc): 1.05

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Cable type: RG 178 B/U, RG 196 A/U

Others

Temp (min / max): -55°C / +250°C


Humidity (max): <=95% [at 60 deg C /140 F]

Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [6 ms] Salt Spray Corrosion: >1000 hr Climatical Category: 50/175/21 Shielding (min): 75 dB (10 MHz) Shielding (min): 40 dB (1 GHz)

IP Rating: 50

DRAWINGS

Draws





Dimensions

	А	L	М	S 1	S2
mm.	12	43	32	10	9
in.	0,47	1,69	1,26	0,39	0,35

RECOMMENDED BY LEMO

Tools

Extractor: -

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Coax Tool: DCC.91.019.1LA Die Tool: DPE.99.025.45K

Spanner wrench: DCD.1B.015.PA090

Caps: BFG.1B.100.PCSG

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.