

SUMMARY

Wires

Low	3
High	0
Coax	0
Triax	0
Quad	0
Fiber	0
Fluidic	0



Image is for illustrative purpose only

Download

[Request a quote](#)

[Catalog](#)

Series

Termination type	Male crimp
IP rating	68
Cable Ø	7.60 - 8.00 mm
Matching parts	EGG.3K.303.CYM
Status	active

Alternative part

TECHNICAL DETAILS

Mechanics

Shell Style/Model	FG*: Straight plug, cable adapter and nut for fitting a bend relief
Keying	1 key (alpha=0, plug: male contacts, receptacle: female contacts)
Housing Material	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
Cable Fixing	∅ 7.6 - 8 mm
Variant	Z : Nut for fitting a bend relief

Performance

Configuration	3K.303 : 3 Low Voltage
Insulator	Y: PEEK for crimp contacts
Rated Current	25 Amps

Specifications

Contact Type: Crimp
Max. Matings: 5000
Contact Retention: 65 N

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.


Contact Dia.: 2 mm (0.079in)
 Bucket Dia.: 2.4 mm (0.094in)
 Min. Conductor: 1.5 mm² (AWG 16)
 Max. Conductor: 2.5 mm² (AWG 12)
 R (max): 3.3 mOhm
 Vtest (contact-shell): 2650 V (AC), 3750 V (DC)
 Vtest (contact-contact): 3200 V (AC), 4530 V (DC)

Others

Humidity (max): ≤95% [at 60 deg C /140 F]
 Vibration: 15 g [10 Hz - 2000 Hz]
 Shock Resistance: 100 g [6 ms]
 Salt Spray Corrosion: >1000 hr
 Climatical Category: 50/175/21
 Shielding (min): 95 dB (10 MHz)
 Shielding (min): 80 dB (1 GHz)
 IP Rating: 68

DRAWINGS

Draws



Dimensions

	A	L	M	S2
mm.	19	60	40	15
in.	0,75	2,36	1,57	0,59

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

RECOMMENDED BY LEMO

Tools

Crimp Tool: DPC.91.101.A
Crimp settings: AWG/Selector = 12-14-16/7-6-5
Positionner: DCE.91.203.BVCM
Extractor: DCC.91.202.5LA
Replacement contact: FGG.3B.575.ZZC
Spanner wrench: DCD.3E.030.PA150
Caps: BFG.3K.100.NAS

Cables

CMN.03.T14.078PGCE			
330 150	PVC	Grey	

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.