

www.lemo.com

SUMMARY

Wires

 Low
 0

 High
 0

 Coax
 0

 Triax
 0

 Quad
 0

 Fiber
 0

 Fluidic
 0

Series 00

Termination type No contacts / Accessory

IP rating 0

Cable Ø 2.50 - 2.80 mm

Matching parts

Status active

Alternative part



Image is for illustrative purpose only

Download

Request a quote

Catalog

TECHNICAL DETAILS

Mechanics

Shell Style/Model GMB*: Bend relief Green

Keying No keying

Housing Material Thermoplastic polyurethane elastomer(Desmopan 786)

Weight .42 g

Performance

Configuration

Insulator


Rated Current

Others

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

DRAWINGS

Draws



No keying

Dimensions

	Α	L
mm.	2.5	22
in.	0,10	0,87

RECOMMENDED BY LEMO

Tools

None

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.