

www.lemo.com

PAA.M1.4GL.AC65GZ

SUMMARY

Wires

Triax

 Low
 14

 High
 0

 Coax
 0

Quad 0

0

Fiber 0
Fluidic 0

Series P

Termination type Male solder

IP rating 50

Cable Ø 5.30 - 6.50 mm

Matching parts PLA.M1.4GL.LG

Status active

Alternative part



Image is for illustrative purpose only

Download

Request a quote

Catalog

TECHNICAL DETAILS

Mechanics

Shell Style/Model PA*: Straight plug with cable collet and nut for fitting a bend relief

Keying 2 keys (alpha=40; Plug: male contacts; Receptacle: female contacts)

Housing Material PSU (Polysulfone), gray

Cable Fixing : 5.3 - 6.5 mm

Variant G: Gray collet nut for bend relief

Weight 5.00 g

Performance

Configuration 1P.M14: 14 Low Voltage

Insulator

Rated Current 2 Amps

Specifications

Contact Type: Solder Max. Matings: 2000

Contact Dia.: 0.5 mm (0.0201in)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Bucket Dia.: 0.45 mm (0.018in)

Max. Solid Conductor: 0.09 mm² (AWG 28) Max. Stranded Conductor: 0.09 mm² (AWG 28)

R (max): 8.5 mOhm

Test voltage (kV rms) Contact-contact: 0.6


Air clearance min. (mm) or Creepage distance min. (mm): 0.5


Others

F ret (min): 50 N F ret (max): 150 N IP Rating: 50

DRAWINGS

Draws







Dimensions

	А	L	S1
mm.	14	48	S9
in.	0,55	1,89	

RECOMMENDED BY LEMO

Tools

None

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Cables

CMN.14.T28.056PGCE	PVC	GREY	
CMN.14.T28.056PGZE		Grey	
CMN.14.T28.056PNCE	PVC	Black	
CMN.14.T28.056PNZE			
CMN.14.T28.056QGZE	TPR (medical)	Grey	>

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.