

PCA.0A.250.NTLC29Z

Image is for illustrative purpose only

SUMMARY

Wires

Low 0
High 0

Coax

Triax 0

Quad 0

Fiber 0

Fluidic 0

Series 0A

Termination type Female solder

IP rating 50

Cable Ø 2.50 - 2.80 mm

Matching parts FFA.0A.250.NTAC29Z

Status active

Alternative part

TECHNICAL DETAILS

Mechanics

Shell Style/Model PCA*: Straight receptacle with cable collet and nut for fitting a bend relief

Download

Catalog

Request a quote

Keying

Housing Material Brass (nickel plated) shell, collet nut, latch sleeve and mid pieces

Cable Fixing : 2.5 - 2.8 mm

Variant Z: Nut for fitting a bend relief

Weight 8.73 g

Performance

Configuration 0.25 : 1 Coax (50 Ohm)

Insulator

Rated Current

Specifications

Contact Type: Coaxial 50 Ohm (Solder)

Max. Matings: 1000


LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Others

IP Rating: 50

DRAWINGS

Draws





Dimensions

	А	В	L	S1	S2	S 3
mm.	9	11	36.5	8	9	9
in.	0,35	0,43	1,44	0,31	0,35	0,35

RECOMMENDED BY LEMO

Tools

None

Cables

017 420	PVC	Black	
017 450	COPOLYMER	Black	
018 700	PTFE	White	
018 800	PTFE	White	
031 600	PTFE	Brown	

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

CCX.50.RG1.74-U25N	PVC	Black	
CCX.50.RG1.74AU28N	PVC	Black	
CCX.50.RG1.74AU28N	PVC	Black	
CCX.50.RG1.74U25N	PVC	Black	
CCX.50.RG1.88AU26B	PFA	White	
CCX.50.RG1.88AU26B	PTFE	White	
CCX.50.RG3.16BU26M	FEP	Brown	
CCX.50.RG3.16U28M	PTFE	Brown	
CCX.75.RG1.79BU26M	FEP	Brown	
CCX.75.RG1.87AU26B	PFA	White	
CCX.75.RG1.87AU27B	PTFE	White	

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.