

PCA.0S.650.CTLC32

SUMMARY

# Wires			
Low	0		
High	0		
Coax	0		Image is for illustrative purpose only
Triax	1	Download	
Quad	0	Request a quote	
Fiber	0	Catalog	
Fluidic	0		
Series	OS		
Termination type	Female solder		
IP rating	50		
Cable Ø	2.30 - 3.20 mm		
Matching parts	FFA.0S.650.CLAC32		
Status	active		
Alternative part			

TECHNICAL DETAILS

Mechanics

Shell Style/Model	PCA*: Free receptacle, cable collet			
Keying	ircular (can rotate), plug has male contact(s)			
Housing Material	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces			
Cable Fixing	: 2.3 - 3.2 mm			
Variant				
Weight	8.72 g			
Performance				
Configuration				

Configuration	0S.650 : 1 Triax (50 Ohm)		
Insulator	T: PTFE		
Rated Current	6 Amps		

Specifications

Contact Type: Triaxial 50 Ohm (Solder) Max. Matings: 1000 Contact Dia.: 0.9 mm (0.035"in)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.


Vtest: 1200 V (AC), 1700 V (DC) Impedance: 50 Ohm VSWR: 1.03 + 0.34 * f/GHz Cable type: RGT 178, RGT 174

Others

Endurance (Shell): 5000 mating cycles Temp (min / max): -55°C / +250°C Humidity (max): <=95% [at 60 deg C /140 F] Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [6 ms] Salt Spray Corrosion: >144 hr Climatical Category: 50/175/21 Shielding (min): 75 dB (10 MHz) Shielding (min): 40 dB (1 GHz) IP Rating: 50

DRAWINGS

Draws



 \bigcirc

Dimensions

	А	С	L	S2
mm.	8.9	4.2	33.5	6.5
in.	0,35	0,17	1,32	0,26

RECOMMENDED BY LEMO

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Tools

Spanner wrench: DCD.0S.005.PA065

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.