

SUMMARY

Wires

| | |
|---------|---|
| Low | 4 |
| High | 0 |
| Coax | 0 |
| Triax | 0 |
| Quad | 0 |
| Fiber | 0 |
| Fluidic | 0 |




Image is for illustrative purpose only

Download

[Request a quote](#)

[Catalog](#)

| | |
|------------------|------------------|
| Series | P |
| Termination type | Female print PCB |
| IP rating | 50 |
| Cable Ø | 0.00 - 0.00 mm |
| Matching parts | |
| Status | active |
| Alternative part | |

TECHNICAL DETAILS

Mechanics

| | |
|-------------------|---------------------------------------------------------------------------------|
| Shell Style/Model | PX*: Elbow receptacle key (G) or keys (A,B,C) with two nuts for printed circuit |
| Keying | 2 keys (alpha=60; Plug: male contacts; Receptacle: female contacts) |
| Housing Material | PSU (Polysulfone), black |
| Cable Fixing | ∅ 0 - 0 mm |
| Variant | A : Blue front nut |

Performance

| | |
|---------------|------------------------|
| Configuration | 1P.M04 : 4 Low Voltage |
| Insulator | |
| Rated Current | 8 Amps |

Specifications

| |
|---------------------------------|
| Contact Type: Print (straight) |
| Max. Matings: 2000 |
| Contact Dia.: 0.9 mm (0.0354in) |

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

