muRata Capacitor Data Sheet RCER71E106K3M1H03A "#" indicates a package specification code.					
In Production Power- train Q200 Cmax. Low acoustic Cra		OHS REACH			
< List of part numbers with package codes > RCER71E106K3M1H03A					
Shape		Note	es		
		Meet LF(Lead Free)[*LF : Lead content is less than 1000 ppm.], HF(Halogen Free)			
		References			
		Packaging	Specifications	Minimum quantity	
		А	Ammo pack taping type	1500	
		-			
L size or outer diameter D (mm)	5.5 mm max.	_			
W size	5.0 mm max.				
T size	4.0 mm max.				
Lead spacing F	5.0 +0.6/-0.2mm				

0.5 ±0.05mm

7.5mm

Specifications

Lead diameter d

W1 size (max.)

Capacitance	10µF±10%
Rated voltage	25Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	±15%
Temperature range of temperature characteristics	-55 to 125°C
Operating temperature range	-55 to 125°C

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

