muRata Capacitor Data Sheet RCER72A681K0DBH03A "#" indicates a package specification code.					
In Production Power- Canax AEC- 0200 Cmax LOW acoustic Cmax Deflecting Crack Crack Crack Reach Flow OK Welding RoHS REACH					
< List of part numbers with package codes > RCER72A681K0DBH03A					
Shape		Note	es		
		Meet LF(Lead Free)[*LF : Lead content is less than 1000 ppm.], HF(Halogen Free)			
		Packaging	Specifications Ammo pack taping type	Minimum quantity	
L size or outer diameter D (mm)	3.6 mm max.				
W size	3.5 mm max.				
T size	2.5 mm max.				
Lead spacing F	2.5 +0.4/-0.2mm				
Lead diameter d	0.5 ±0.05mm				

Specifications

Capacitance	680pF±10%
Rated voltage	100Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	±15%
Temperature range of temperature characteristics	-55 to 125°C
Operating temperature range	-55 to 125°C

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.