



## UBT

### ■ Dimensions

V(Code)		10 (1A)			16 (1C)			25 (1E)			35 (1V)			50 (1H)		
Cap. (μF)	Item Code	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA <sub>rms</sub> )
4.7	4R7															
10	100													8 × 11.5	1.15	85
22	220													8 × 11.5	0.75	180
33	330													8 × 11.5	0.50	250
47	470													8 × 11.5	0.45	300
100	101				8 × 11.5	0.32	340	8 × 11.5	0.13	500				8 × 11.5	0.35	440
220	221	8 × 11.5	0.26	340	10 × 12.5	0.15	620	10 × 12.5	0.10	680	10 × 16	0.094	790	10 × 20	0.18	555
330	331	10 × 12.5	0.15	620	10 × 12.5	0.10	680	10 × 16	0.075	945	10 × 20	0.075	950	12.5 × 20	0.098	930
470	471	10 × 12.5	0.10	680	10 × 16	0.075	945	10 × 20	0.057	1100	12.5 × 20	0.058	1330	12.5 × 25	0.070	1330
1000	102	10 × 20	0.057	1100	12.5 × 20	0.042	1490	12.5 × 25	0.033	1750	16 × 25	0.031	2010	16 × 31.5	0.031	2430
2200	222	12.5 × 25	0.033	1750	16 × 25	0.024	2300	16 × 31.5	0.020	2710	18 × 35.5	0.025	2790			
3300	332	16 × 25	0.024	2300	16 × 31.5	0.020	2710	18 × 31.5	0.017	3310						
4700	472	16 × 31.5	0.020	2710	18 × 31.5	0.018	3270									

V(Code)		63 (1J)			80 (1K)			100 (2A)		
Cap. (μF)	Item Code	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Impedance (Ω) MAX.	Rated ripple (mA <sub>rms</sub> )
10	100							8 × 11.5	1.50	150
22	220	8 × 11.5	2.00	130	8 × 11.5	1.50	150	10 × 12.5	0.80	480
33	330	8 × 11.5	1.50	150	10 × 12.5	0.80	480	10 × 12.5	0.80	480
47	470	10 × 12.5	0.59	530	10 × 12.5	0.80	480	10 × 16	0.55	630
100	101	10 × 16	0.41	690	10 × 20	0.39	790	12.5 × 20	0.25	990
220	221	12.5 × 20	0.16	1050	12.5 × 25	0.18	1240	16 × 25	0.11	1500
330	331	12.5 × 25	0.12	1290	12.5 × 31.5	0.16	1390	16 × 31.5	0.079	1790
470	471	12.5 × 31.5	0.097	1460	16 × 25	0.11	1500			

Rated ripple current (mA<sub>rms</sub>) at 125°C 100kHz  
Impedance (Ω) MAX. at 20°C 100kHz

### ● Frequency coefficient of rated ripple current

V	CV	Frequency	120Hz	300Hz	1kHz	10kHz or more
10 to 100		1000 > CV	0.50	0.64	0.83	1.00
		1000 ≤ CV	0.67	0.79	0.91	1.00

V(Code)		160 (2C)		200 (2D)		250 (2E)		350 (2V)		400 (2G)		450 (2W)	
Cap. (μF)	Item Code	Case size φD × L (mm)	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Rated ripple (mA <sub>rms</sub> )	Case size φD × L (mm)	Rated ripple (mA <sub>rms</sub> )
4.7	4R7							10 × 20	53	10 × 20	53	10 × 25	58
10	100			10 × 20	78	10 × 20	78	10 × 25	85	10 × 25	86	12.5 × 20	86
22	220	10 × 20	115	10 × 25	126	12.5 × 20	128	12.5 × 25	139	12.5 × 31.5	142	16 × 25	154
33	330	10 × 25	154	12.5 × 20	157	12.5 × 25	171	16 × 25	189	16 × 25	189	16 × 31.5	203
47	470	12.5 × 20	187	12.5 × 25	204	16 × 25	225	16 × 31.5	243	16 × 31.5	243		
68	680	12.5 × 25	245	16 × 20	250	16 × 31.5	292						
100	101	16 × 25	329	16 × 25	329								
150	151	16 × 31.5	434										

Rated ripple current (mA<sub>rms</sub>) at 125°C 120Hz

### ● Frequency coefficient of rated ripple current

V	Cap. (μF)	Frequency	50Hz	120Hz	300Hz	1kHz	10kHz	100kHz or more
160 to 450		4.7 to 33	0.75	1.00	1.25	1.50	1.75	1.80
		47 to 150	0.80	1.00	1.15	1.30	1.40	1.50